

RECORD 10-634

CURRENT CODE WORDING

ERRATA

CC-3842.10 Minimum Dimensions. The minimum dimensions of Fig. CC-4542.2-1 through Fig. CC-4542.2-7 shall be met where:

$r_1 = \frac{1}{4}t$ or $\frac{3}{4}$ in. (19 mm), whichever is less

$r_2 = \frac{1}{4}$ in. (6 mm) min.

t = nominal thickness of liner

t_a = nominal thickness of attachments to liner

$t_c = 0.7t_n, 0.7t_1, 0.7t_a$, or $\frac{1}{4}$ in. (6 mm), whichever is less

t_{\min} = the smaller of $\frac{3}{4}$ in. (19 mm) or the thickness of the thinner of the parts joined

t_n = nominal thickness of penetrating part

$t_w = 0.7t_{\min}$

t_1, t_2 = not less than the smaller of $\frac{1}{4}$ in. (6 mm) or $0.7t_{\min}$

$t_1, t_2 \geq 1\frac{1}{4} t_{\min}$

Replace the last three lines with the following:

t_1 or t_2 = not less than the smaller of $\frac{1}{4}$ in.
(6 mm) or $0.7t_{\min}$
 $t_1 + t_2 \geq 1\frac{1}{4} t_{\min}$