

Section III

Section III

TABLES

| | | |
|------|---|------|
| 1A | Section I; Section III, Classes 2 and 3; Section VIII, Division 1; and Section XII Maximum Allowable Stress Values, S , for Ferrous Materials | 8 |
| 1B | Section I; Section III, Classes 2 and 3; Section VIII, Division 1; and Section XII Maximum Allowable Stress Values, S , for Nonferrous Materials | 164 |
| 2A | Section III, Division 1, Classes 1, MC, and CS; Section III, Division 3; and Section VIII, Division 5 Design Stress Intensity Values, S_m , and Section VIII, Division 2, Class 1 Maximum Allowable Stress Values, S , for Ferrous Materials | 296 |
| 2B | Section III, Division 1, Classes 1, MC, and CS; Section III, Division 3; and Section VIII, Division 5 Design Stress Intensity Values, S_m , and Section VIII, Division 2, Class 1 Maximum Allowable Stress Values, S , for Nonferrous Materials | 382 |
| 3 | Section III, Division 1, Classes 2 and 3; Section VIII, Divisions 1 and 2; and Section XII Maximum Allowable Stress Values, S , for Bolting Materials | 410 |
| 4 | Section III, Division 1, Classes 1 and MC; Section III, Division 3; and Section III, Division 5 Design Stress Intensity Values, S_m , and Section VIII, Division 2 Maximum Allowable Stress Values, S , for Bolting Materials | 440 |
| 5A | Section VIII, Division 2, Class 2 Maximum Allowable Stress Values, S , for Ferrous Materials | 452 |
| 5B | Section VIII, Division 2, Class 2 Maximum Allowable Stress Values, S , for Nonferrous Materials | 514 |
| 6A | Section IV Maximum Allowable Stress Values, S , for Ferrous Materials | 540 |
| 6B | Section IV Maximum Allowable Stress Values, S , for Nonferrous Materials | 548 |
| 6C | Section IV Maximum Allowable Stress Values, S , for Lined Water Heater Materials | 556 |
| 6D | Section IV Maximum Allowable Stress Values, S , for Unlined Water Heater Materials | 562 |
| U | Tensile Strength Values, S_u , for Ferrous and Nonferrous Materials | 568 |
| Y-1 | Yield Strength Values, S_y , for Ferrous and Nonferrous Materials | 776 |
| Y-2 | Factors for Limiting Permanent Strain in Austenitic Stainless Steels, High-Nickel Alloy Steels, Nickel, and Nickel Alloys | 1094 |
| TE-1 | Thermal Expansion for Ferrous Materials | 1096 |
| TE-2 | Thermal Expansion for Aluminum Alloys | 1101 |
| TE-3 | Thermal Expansion for Copper Alloys | 1102 |
| TE-4 | Thermal Expansion for Nickel Alloys | 1103 |
| TE-5 | Thermal Expansion for Titanium Alloys | 1113 |
| TCD | Nominal Coefficients of Thermal Conductivity (TC) and Thermal Diffusivity (TD) | 1114 |
| TM-1 | Moduli of Elasticity E of Ferrous Materials for Given Temperatures | 1128 |
| TM-2 | Moduli of Elasticity E of Aluminum and Aluminum Alloys for Given Temperatures | 1131 |
| TM-3 | Moduli of Elasticity E of Copper and Copper Alloys for Given Temperatures | 1132 |
| TM-4 | Moduli of Elasticity E of High Nickel Alloys for Given Temperatures | 1133 |
| TM-5 | Moduli of Elasticity E of Titanium and Zirconium for Given Temperatures | 1134 |
| PRD | Poisson's Ratio and Density of Materials | 1134 |
| G | Tabular Values for Figure G | 1216 |
| CS-1 | Tabular Values for Figure CS-1 | 1218 |
| CS-2 | Tabular Values for Figure CS-2 | 1219 |
| CS-3 | Tabular Values for Figure CS-3 | 1220 |
| CS-4 | Tabular Values for Figure CS-4 | 1221 |
| CS-5 | Tabular Values for Figure CS-5 | 1221 |
| CS-6 | Tabular Values for Figure CS-6 | 1222 |
| HT-1 | Tabular Values for Figure HT-1 | 1222 |
| HT-2 | Tabular Values for Figure HT-2 | 1223 |
| HA-1 | Tabular Values for Figure HA-1 | 1223 |
| HA-2 | Tabular Values for Figure HA-2 | 1224 |
| HA-3 | Tabular Values for Figure HA-3 | 1224 |
| HA-4 | Tabular Values for Figure HA-4 | 1225 |
| HA-5 | Tabular Values for Figure HA-5 | 1225 |
| HA-6 | Tabular Values for Figure HA-6 | 1226 |
| HA-7 | Tabular Values for Figure HA-7 | 1227 |
| HA-8 | Tabular Values for Figure HA-8 | 1227 |